

CLAIMS

What is claimed is:

1. A communication system for mobile platforms, comprising:
 - a first mobile platform including a first transceiver that is assigned a first Internet Protocol (IP) address;
 - a second mobile platform including a second transceiver that is assigned a second IP address;
 - a ground station that transmits a forward link that contains first and second IP packet data that is modulated by a variable length orthogonal (VLO) spreader and wherein said first and second IP packet data have different information data rates; and
 - a satellite that relays said forward link from said ground station to said first and second mobile platforms.
2. The communications system of claim 1 wherein said ground station includes a packet organizer that groups IP packets based on an information data rate of said IP packets.
3. The communication system of claim 1 wherein said ground station includes a forward error correction (FEC) encoder that applies FEC coding to said first and second IP packet data and wherein said VLO spreader communicates with an output of said FEC encoder.

4. The communication system of claim 3 wherein said ground station includes a pseudonoise (PN) spreader that spreads an output of said VLO spreader.

5. The communication system of claim 4 wherein said first and second mobile platforms include a pseudonoise (PN) despreader that despreads an data received on said forward link.

6. The communication system of claim 5 wherein said first and second mobile platforms include a VLO despreader that despreads an output of said PN despreader.

7. The communication system of claim 6 wherein said first and second mobile platforms include a FEC decoder that decodes an output of said PN despreader.

8. The communication system of claim 7 wherein said ground station selects a first VLO spreading code to optimize a first desired link margin of said first transceiver and a second VLO spreading code is selected to optimize a second desired link margin of said second transceiver.

9. The communication system of claim 8 wherein said first transceiver includes a feedback circuit that generates a link margin estimate for said first IP packet received by said first transceiver.

10. The communication system of claim 9 wherein said ground station receives said link margin estimate and adjusts said information data rate of subsequent IP packets.

11. The communication system of claim 10 wherein said feedback circuit of said first transceiver includes:

a signal estimator that generates a bit energy signal; and

a noise estimator that generates a noise estimate signal.

12. The communication system of claim 11 wherein said feedback circuit transmits said link margin estimate to said ground station.

13. The communication system of claim 12 wherein said ground station adjusts said VLO spreading code to optimize said link margin of said first transceiver.

14. The communication system of claim 13 wherein said ground station adjusts said VLO spreading code and FEC coding of said FEC encoder to optimize said link margin of said first transceiver.

15. The communication system of claim 13 wherein said VLO code despreaders responds to VLO timing sequence data contained in an overhead portion of an output of said PN despreaders.

16. The communication system of claim 1 wherein said first IP packet is addressed to said first transceiver located on said first mobile platform and said second IP packet is addressed to said second transceiver located on a second mobile platform.

17. The communication system of claim 1 wherein said forward link includes first and second broadcast frames that are transmitted concurrently.

18. The communication system of claim 17 wherein said concurrent broadcast frames have distinct VLO codes and substantially the same signal strength.

19. A method for communicating with mobile platforms, comprising:

- assigning a first Internet Protocol (IP) address to a first mobile platform including a first transceiver;
- assigning a second IP address to a second mobile platform including a second transceiver;
- transmitting a forward link that contains first and second IP packet data from a ground station;
- modulating said first and second IP packets with a variable length orthogonal (VLO) code using a VLO spreader, wherein said first and second IP packet data have different information data rates; and
- relaying said forward link from said ground station to said first and second mobile platforms using a satellite.

20. The method of claim 19 further comprising organizing IP packets at said ground station based on an information data rate of said IP packets.

21. The method of claim 19 further comprising applying forward error correction (FEC) coding prior to said step of modulating.

22. The method of claim 21 further comprising spreading an output of said VLO spreader using a pseudonoise (PN) spreader.

23. The method of claim 22 further comprising despreading data received on said forward link using a PN despreader of said first and second mobile platforms.

24. The method of claim 23 further comprising despreading an output of said PN despreader using a VLO despreader.

25. The method of claim 24 further comprising decoding an output of said FEC decoder using a FEC decoder of said first and second mobile platforms.

26. The method of claim 25 further comprising:
selecting a first VLO spreading code to optimize a first desired link margin of said first transceiver; and
selecting a second VLO spreading code to optimize a second desired link margin of said second transceiver.

27. The method of claim 26 further comprising:
generating a link margin estimate for said first IP packet received by said first transceiver; and
transmitting said link margin estimate to said ground station.

28. The method of claim 27 further comprising:

receiving said link margin estimate at said ground station; and
adjusting said information data rate of said subsequent IP packets.

29. The method of claim 28 wherein said step of generating said link margin estimate further comprises:

generating a bit energy signal; and
generating a noise estimate signal.

30. The method of claim 29 further comprising adjusting said VLO spreading code to optimize said link margin of said first transceiver.

31. The method of claim 29 further comprising adjusting said VLO spreading code and said FEC encoding to optimize said link margin of said first transceiver.

32. The method of claim 30 further comprising responding to VLO timing sequence data contained in an overhead portion of an output of said PN despreaders using said VLO decoder.

33. The method of claim 32 further comprising:
addressing said first IP packet to said first transceiver located on
said first mobile platform; and
addressing said second IP packet to said second transceiver
located on a second mobile platform.

34. The method of claim 19 wherein said forward link includes first and
second broadcast frames that are transmitted concurrently.

35. The method of claim 34 wherein said concurrent broadcast frames
have distinct VLO codes and substantially the same signal strength.